

OVERVIEW

Velvet-Tex is an antique velvet effect coating used for interior surfaces to create luxurious warm interior walls. Using a combination of special effect additives, Velvet-Tex transforms plain walls into vibrant three dimensional surfaces. Velvet-Tex is available in an attractive range of shades.

PROPERTIES

Velvet-Tex is a blend of acrylic polymers, pearlescent pigment and soft-touch additives. The product has the following properties:

- Easy to use
- Provides an attractive pearlescent lustre
- Provides a soft touch velvet effect
- Provides light and dark surface shading
- Can be used directly over painted surfaces
- Excellent wear resistant finish

AREAS OF USE

Velvet-Tex can be used on most interior surfaces such as painted walls. It is suitable for use in hotels, nightclubs, public buildings, as well as in domestic applications.

PREPARATION OF SURFACE

New surfaces: Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be covered. All cracks, chips, voids and damages should be repaired with Handycoat. Prepare surface using Handycoat and sand to a smooth level surface. Use Terralux or equivalent as a base paint for Velvet-Tex application.

Old surfaces: Before applying to old surfaces, ensure the substrate is firm. First wash down the surface with a sugar soap solution, rinse and allow to dry before repairing or applying the primer.

APPLICATION & CLEANING OF TOOLS

Apply Velvet-Tex in 3 coats using stainless steel in-ox trowels, building up layers in a patchwork style application. Allow 2-3 hours to dry between coats.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Velvet-Tex is supplied in 5kg and 20kg plastic containers.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Velvet touch pearlescent effect coating.
Binder	Acrylic.
Thinning	Water if required.
Drying Time	1-2 hours.
Specific Gravity	1.02
Viscosity	40,000cps
Coverage	0.15-0.2kg/m ²
Application Method	Trowel.
Flame Spread	Class 0
Packaging	5kg and 20kg plastic containers.
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

RUSSIA:

OOO Terraco Sweden Ltd, Russia
 Tel: +7 495 1012237
 Fax: +7 495 9273881
 E-mail: terraco@online.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
 Fax: +7 (0)4212 410591
 E-mail: terracoVostok@terraco.khn.ru

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8759 4742
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 6226 8903
 Fax: +86 (0)21 6252 0547
 Email: shanghai@terraco.com.cn
 Web: www.terraco.com.cn

JORDAN:

Jordan Swedish Polymers Industrial Corp.
 Tel: +962 (0)6 552 7140, 5530229, 5514037
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
 Tel: +20 (0)2 3479106, 3024860
 Fax: +20 (0)2 3470895
 E-mail: terraco@terraco.com.eg
 Web: www.terraco.com.eg

UAE:

Terraco UAE Ltd
 Tel: +971 (0) 4 2850999
 Fax: +971 (0)4 2852299
 E-mail: terraco@emirates.net.ae

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
 Tel: +90 (0)222 236 0423 / 24
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

THAILAND:

Terraco Industry (Thailand) Limited
 Tel: +66 (0)2 948 5558
 Fax: +66 (0)2 948 5540
 E-mail: terraco@terraco.co.th

VIETNAM:

Terraco Vietnam Co., Ltd
 Tel: +84 (0)650 820100
 Fax: +84 (0)650 820101
 E-mail: terraco_vietnam@hcm.vnn.vn

SOUTH KOREA:

Terraco Korea Co., Ltd
 Tel: +82 (0) 2 5611551
 Fax: +82 (0)2 5611515
 E-Mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

IRELAND:

Terraco Technical Centre, Ireland
 Tel: +353 (0) 404 66555
 Fax: +353 (0) 404 66654
 E-mail: terraco@eircom.net
 Web: www.terraco.com