

OVERVIEW

Flexipave Line Paint is an acrylic based water-borne paint designed for line marking on the Flexipave Coating System. It is used for tennis courts and other recreational surfaces.

PROPERTIES

Flexipave Line Paint is based on acrylic binder. Special features of the system are as follows:

- Low VOC (volatile organic component) level. Complies with new EPA Regulations of less than 150g/ltr.
- High solids and opacity
- Excellent durability characteristics
- Good dirt pick up resistance
- Excellent substrate adhesion
- Excellent adhesion to old paint

AREAS OF USE

Flexipave Line Paint is designed as a line marking paint for tennis courts and other recreational surfaces. It is specifically designed for use as part of the Flexipave System but performs equally as well when applied directly to asphalt, concrete and previously painted surfaces.

PREPARATION OF SURFACE

To be applied directly on the Flexipave Coating. Allow the Flexipave Coating to dry for 48 hours before applying.

APPLICATION & CLEANING OF TOOLS

Apply using spray, brush or roller. Application should be carried out at a relative humidity below 85% and at a temperature between 7°C to 40°C. The product is applied at a rate of 300grs/m²/coat.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Flexipave line Paint is supplied in 25 kg plastic pails.

Store the paint in a clean, dry area, protected from direct sunlight and extreme heat or cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Acrylic based waterborne line marking paint.
Binder	Acrylic
Colour	White
Viscosity	85 K.U. \pm 5K.U. at 20°C
Specific Weight	1.60
Solid Content	75% by weight.
Volume Solids	60% by volume.
pH Value	8-8.5
Application Method	Roller, brush, spray.
Paint Consumption	300g/m ² /coat.
Packaging	25 kg plastic pails.
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

RUSSIA:

OOO Terraco Sweden Ltd, Russia
 Tel: +7 095 101 2237
 Fax: +7 095 927 3881
 E-mail: terraco@online.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 431 933
 Fax: +7 (0)4212 431 977
 E-mail: terracoVostok@terraco.khn.ru

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8758 2600,
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 6210 2048
 Fax: +86 (0)21 6252 0547
 Email: sales@terraco.com.cn

JORDAN:

Jordan Swedish Polymers Industrial Corp.
 Tel: +962 (0)6 552 7140, 553 0229, 551 4037
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
 Tel: +20 (0)2 8340 004, 832 3584
 Fax: +20 (0)2 8340 004, 832 3584
 E-mail: terraco@terraco.com.eg

UAE:

Terraco UAE Ltd
 Tel: +971 (0)6 543 3565
 Fax: +971 (0)6 543 3558
 E-mail: terraco@emirates.net.ae

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
 Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

THAILAND:

Terraco Industry (Thailand) Limited
 Tel: +66 (0)2 948 5558
 Fax: +66 (0)2 948 5540
 E-mail: terraco@terraco.co.th

VIETNAM:

Terraco Vietnam Co., Ltd
 Tel: +84 (0)650 820100
 Fax: +84 (0)650 820101
 E-mail: terraco_vietnam@hcm.vnn.vn

SOUTH KOREA:

Terraco Korea Co., Ltd
 Tel: +82 (0)43 645 8814
 Fax: +82 (0)43 643 9429
 E-Mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

IRELAND:

Terraco Technical Centre, Ireland
 Tel: +353 (0) 404 66555
 Fax: +353 (0) 404 66654
 E-mail: terraco@eircom.net
 Web: www.terraco.com