

OVERVIEW

Monocote is a coloured mineral plaster, which is applied in a single coat to give an attractive decorative finish. Monocote is water repellent, while at the same time allowing the structure to breathe. Monocote has excellent dirt pick-up resistance and is extremely stable against UV light even in severe climatic conditions. Monocote can either be applied manually or by machine and is available in a range of sixteen standard colours.

PROPERTIES

Monocote is formulated using a mixture of precisely graded fillers, hydraulic binders, pigments and additives. Monocote is finished by removing the top layer of material using a scratch trowel when the material has partially set. This exposes the aggregate to provide an attractive textured surface. The finished Monocote plaster has the following characteristics.

- Long life
- Dirt pick-up resistance
- Excellent UV stability
- Water repellent
- Plastering / finishing in one operation
- Good mechanical strength

AREAS OF USE

Monocote is primarily designed for exterior facades for direct application on clay brick, concrete block, AAC block, precast/in-situ concrete and stone. Monocote can also be used on interior facades.

PREPARATION OF SURFACE

Ensure all dust, dirt and foreign matter are brushed and scraped away. Also ensure surface is solid, free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be coated. Apply a coat of penetrating primer to absorbent surfaces such as AAC blocks.

A key coat is required on very smooth surfaces such as precast or in-situ concrete (1pt Monocote, 0.4 pts. water, 0.08 pts. Terrabond A).

MIXING

Using a high speed mixer, mix 25kg of Monocote with 4.5 ltr of water. Mix for 3 minutes. Ensure that mixing time and ratio of powder/water are constant to ensure colour consistency. Allow material to stand for 5 minutes, remix and use. Prepared material should be used within 4 hours.

APPLICATION & CLEANING OF TOOLS

Saturate the substrate with water to reduce suction of water from the product the day before application and again 1 hour before application. Apply by spray or by hand and level the surface using standard plastering techniques. Allow the material to "set-up" and finish the surface with a scratch trowel to remove the top layer of material.

Clean tools and equipment with water after use.

PRECAUTIONS

Do not apply below 8°C as there is risk of efflorescence.

Do not apply on horizontal or sloping surfaces.

Do not apply on gypsum based substrates.

Do not use at ground level to avoid staining.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Monocote is supplied in 25kg bags.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 6 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Decorative single coat mineral plaster.		
Filler Material	Crushed, precisely graded extenders.		
Binder	Hydraulic.		
Pigments	Characterised as fast to light, lime, salt and cement.		
Consumption Rate	1.55KG/m ² /mm thickness.		
Typical Rates		Thickness	Consumption (kg/m²)
	Clay brick	15-20mm	23-31
	Concrete blocks	12-15mm	18-23
	AAC blocks	8-12mm	12-18
Adhesion to Concrete Block	>0.4MPa.		
Adhesion to Clay Block	>0.4MPa.		
Fire Rating	Class M0 (incombustible).		
Colours	16 standard colours.		
Packaging	25kg bags.		
Storage	6 months in original unopened containers.		

For technical enquiries please contact your nearest Terraco representative:

RUSSIA:

OOO Terraco Sweden Ltd, Russia
 Tel: +7 095 101 2237
 Fax: +7 095 927 3881
 E-mail: terraco@online.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 431 933
 Fax: +7 (0)4212 431 977
 E-mail: terracoVostok@terraco.khn.ru

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8758 2600,
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 6210 2048
 Fax: +86 (0)21 6252 0547
 Email: sales@terraco.com.cn

JORDAN:

Jordan Swedish Polymers Industrial Corp.
 Tel: +962 (0)6 552 7140, 553 0229, 551 4037
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
 Tel: +20 (0)2 8340 004, 832 3584
 Fax: +20 (0)2 8340 004, 832 3584
 E-mail: terraco@terraco.com.eg

UAE:

Terraco UAE Ltd
 Tel: +971 (0)6 543 3565
 Fax: +971 (0)6 543 3558
 E-mail: terraco@emirates.net.ae

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
 Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

THAILAND:

Terraco Industry (Thailand) Limited
 Tel: +66 (0)2 948 5558
 Fax: +66 (0)2 948 5540
 E-mail: terraco@terraco.co.th

VIETNAM:

Terraco Vietnam Co., Ltd
 Tel: +84 (0)650 820100
 Fax: +84 (0)650 820101
 E-mail: terraco_vietnam@hcm.vnn.vn

SOUTH KOREA:

Terraco Korea Co., Ltd
 Tel: +82 (0)43 645 8814
 Fax: +82 (0)43 643 9429
 E-Mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

IRELAND:

Terraco Technical Centre, Ireland
 Tel: +353 (0) 404 66555
 Fax: +353 (0) 404 66654
 E-mail: terraco@eircom.net
 Web: www.terraco.com