

OVERVIEW

Terraco Siltop is a premium quality exterior masonry paint based on silicone polymers which provide the coating with excellent dirt pick-up resistance and water repellence. Terraco Siltop is designed for application on highly profiled surfaces such as Terracoat Textured Coatings where it significantly improves the dirt pick-up resistance of the coating. Terraco Siltop has a matt finish and is available in a standard range of 50 colours.

PROPERTIES

Terraco Siltop is based on silane-siloxane polymers which provide the coating with the following unique properties:

- High water vapour transmission
- Excellent breathability
- Excellent dirt pick-up resistance
- Distinctive water beading effect
- Combined with specially graded filler, ensures film integrity over textured surfaces
- Excellent exterior durability
- Excellent coverage
- Low material consumption
- Mould resistant
- Extra long life

AREAS OF USE

TERRACO Siltop is used as an alternative to exterior masonry paint where high performance is required.

Terraco Siltop is used as a top coating system for textured surfaces to minimise the dirt pick-up problems normally associated with open pore textures.

PREPARATION OF SURFACE

New surfaces: Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be covered. All cracks, chips, voids and damages should be repaired with Terraco Acrylic Filler.

Old surfaces: Before applying to old surfaces, ensure the substrate is firm. First wash down the surface with a sugar soap solution, rinse and allow to dry before repairing or applying the primer.

PRIMING

Priming should be done using TERRACO Silprime

APPLICATION & CLEANING OF TOOLS

When applying to old painted surfaces, first wash down with a soda/water solution, rinse and allow to dry before either patching or painting. Very porous substrates should be filled and may require a diluted first coat. Apply the paint by brush, roller or spray. The application should be continuous in order to avoid dry edges; therefore plan the application work accordingly. One or two coats is normally enough to give full coverage at a consumption rate of 0.3-0.4kg/m².

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Product is supplied in 5kg and 20kg plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Exterior silicone based emulsion paint..
Binder	Silane/siloxane .
Pigments	Lime and light-fast. Weather and pollution-resistant.
Additives	Bactericides, anti-corrosion, anti-foam agents, etc.
Viscosity	10,000cps
Specific Weight	55% by weight
Solid Content	55% ± 3%
pH Value	8-9
Water Vapour Permeability (wet cup) sd. Value (m)	0.04
Liquid Water Transmission Rate W24-Value (kg/m²/h 0.5)	0.06
Adhesion Strength (N/mm²)	2.7
Silicone/Acrylic Ratio	0.9:1.0
Wet Scrubs	>10,000
Application Method	Spray (airless or conventional), brush or roller.
Material Consumption	0.3-0.4kg/m ²
Finish	Matt.
Colours	According to <i>TERRACO</i> colour charts. Any special colours can be matched on request.
Packaging	5kg and 20kg plastic pails.
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

RUSSIA:

OOO Terraco Sweden Ltd, Russia
Tel: +7 095 101 2237
Fax: +7 095 927 3881
E-mail: terraco@online.ru
Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 431 933
Fax: +7 (0)4212 431 977
E-mail: terracoVostok@terraco.khn.ru

CHINA:

Terraco Architectural Coatings China Co., Ltd.
Tel: +86 (0)20 8758 2600,
Fax: +86 (0)20 8526 8056
E-mail: sales@terraco.com.cn
Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 6210 2048
Fax: +86 (0)21 6252 0547
Email: sales@terraco.com.cn

JORDAN:

Jordan Swedish Polymers Industrial Corp.
Tel: +962 (0)6 552 7140, 553 0229, 551 4037
Fax: +962 (0)6 553 6560
E-mail: terraco@nol.com.jo
Web: www.terraco.jo

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
Tel: +20 (0)2 8340 004, 832 3584
Fax: +20 (0)2 8340 004, 832 3584
E-mail: terraco@terraco.com.eg

UAE:

Terraco UAE Ltd
Tel: +971 (0)6 543 3565
Fax: +971 (0)6 543 3558
E-mail: terraco@emirates.net.ae

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
Tel: +90 (0)222 236 0423
Fax: +90 (0)222 236 0425
E-mail: terraco@terraco.com.tr
Web: www.terraco.com.tr

THAILAND:

Terraco Industry (Thailand) Limited
Tel: +66 (0)2 948 5558
Fax: +66 (0)2 948 5540
E-mail: terraco@terraco.co.th

VIETNAM:

Terraco Vietnam Co., Ltd
Tel: +84 (0)650 820100
Fax: +84 (0)650 820101
E-mail: terraco_vietnam@hcm.vnn.vn

SOUTH KOREA:

Terraco Korea Co., Ltd
Tel: +82 (0)43 645 8814
Fax: +82 (0)43 643 9429
E-Mail: terraco@terraco.co.kr
Web: www.terraco.co.kr

IRELAND:

Terraco Technical Centre, Ireland
Tel: +353 (0) 404 66555
Fax: +353 (0) 404 66654
E-mail: terraco@eircom.net
Web: www.terraco.com