

OVERVIEW

Terraco Sil is a range of ready-mixed, acrylic/silicone resin bound, textured coatings. It provides the unique combination of a quality architectural finish with outstanding economy through ease of application, a low material consumption rate and surface durability characterised by outstanding water repellence. Terracoat Sil is guaranteed for 10 years against peeling and fading. Terracoat Sil adheres to most exterior and interior surfaces including plywood, chipboard, anti-rust primed steel, gypsum and dry wall. Priming is not required. Terracoat Sil has been developed for use in areas of extreme climatic conditions such as the tropics, where high humidity is prevalent. Overcoating by silicone based or conventional overcoats when required is perfectly acceptable.

PRODUCT GRADES/CODES

G	61313
Smooth	61323
Superfine	61334
Fine	61343
Normal	61353
Decor	61373
Coarse	61383
Random	61403
Excel	61413
Granule	61423

PROPERTIES

Terracoat Sil is formulated from crushed and precisely graded fillers, a combination of acrylic and silicone resin binders and additives which gives it elastic properties, outstanding water repellence, water resistance and water vapour permeability, long life and durability against colour fading and pollution. Terracoat Sil is manufactured in a range of 50 colours. Grades are as follows:

G

Terracoat Sil G is a low build roller applied lightly grained textured coating. Consumption rates are low making it a very economical finish.

Smooth

Terracoat Sil Smooth is a low build roller applied lightly textured coating. Consumption rates are low making it a very economical finish.

Superfine

Terracoat Sil Superfine is a roller/spray applied texture which can be used in a wide range of finishes depending on the application method and material consumption. Finishes vary from fine spray to roller stucco.

Fine

Terracoat Sil Fine is a low to medium build pattern applied by spray or roller.

Normal

Terracoat Sil Normal is a medium build textured finish applied by spray. A medium build spray pattern is the most popular finish.

Decor

Terracoat Sil Decor is a high build textured finish applied by decorative roller or hopper gun. The most popular finishes are roller stucco and coarse spray pattern.

Coarse

Terracoat Sil Coarse is a coarse grained textured coating applied by spray.

Random

Terracoat Sil Random is a trowel applied texture giving an alpine scratch finish. Random has excellent application characteristics, particularly on difficult substrates. It shows a lower density scratch pattern.

Excel

Terracoat Sil Excel is a trowel applied texture giving an alpine scratch finish. Terracoat Sil Excel is specifically designed for application in E.I.F.S. systems.

Granule

Terracoat Sil Granule is a trowel applied texture giving a granular finish.

AREA OF USE

Terracoat Sil is primarily designed for exterior facades and surfaces of buildings such as commercial and industrial complexes, office projects, factories, hospitals and housing developments. It gives a decorative finish to fairfaced concrete walls, pillars, columns, etc.

Terracoat Sil can be used on surfaces of concrete, cement, rendering, lightweight concrete, fairfaced stonework, brickwork, blockwork, plywood, antirust primed steel and galvanised steel. The coating performs equally well on interior surfaces of gypsum dry wall and chipboard.

PREPARATION OF SURFACE

Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges, and protect all adjacent surfaces not to be covered. All cracks, chips, voids and damages should be repaired. TERRACO Handycoat Exterior is recommended. Before applying Terracoat Sil to old surfaces, ensure the substrate is firm. First wash down the surface with a soda / water solution, rinse and allow to dry before repairing or applying the first coat.

PRIMING

Prime surface using TERRACO Silprime.

APPLICATION & CLEANING OF TOOLS

By brush, roller or spray. Ensure areas not requiring coating are masked if spraying. Roller application is done using a series of decorative rollers to achieve different textures.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Terraco Sil is supplied in 25kg plastic pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Acrylic/silicone resin based textured coating.
Binder	Acrylic and silicone resins.
Thinning	Water if required.
Drying Time	3 - 4 hours.
Toxicity	Non-toxic.
Water Diffusion (SIS 021582)	0.05 g/sq. mt.
Flame Spread	Class 0 ASTM E84-81H
Colours	50 standard colours.
Storage	12 months in original unopened containers.

Grade	Specific Gravity	Viscosity ('000 cps.)	Material consumption (Kg / m2)	Application method	Pack sizes (Kg.)
G	1.65	50-60	0,5-0,7	Roller	25
Smooth	1.65	55-65	0,6-0,9	Roller	25
Superfine	1.45	50-60	0,6-3,5	Spray, Roller	25
Fine	1.65	50-60	1,0-1,2	Spray, roller	25
Normal	1.65	50-60	1,5-2,0	Spray	25
Decor	1.65	55-65	2,5-3,5	Spray, roller	25
Coarse	1.65	30-40	2,0-3,0	Spray	25
Random	1.65	50-60	2,2-2,5	Trowel	25
Excel	1.70	35-45	2,2-2,5	Trowel	25
Granule	1.65	30-40	2,1-2,4	Trowel	25

For technical enquiries please contact your nearest Terraco representative:

RUSSIA:

OOO Terraco Sweden Ltd, Russia
Tel: +7 095 101 2237
Fax: +7 095 927 3881
E-mail: terraco@online.ru
Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 431 933
Fax: +7 (0)4212 431 977
E-mail: terracoVostok@terraco.khn.ru

CHINA:

Terraco Architectural Coatings China Co., Ltd.
Tel: +86 (0)20 8758 2600,
Fax: +86 (0)20 8526 8056
E-mail: sales@terraco.com.cn
Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 6210 2048
Fax: +86 (0)21 6252 0547
Email: sales@terraco.com.cn

JORDAN:

Jordan Swedish Polymers Industrial Corp.
Tel: +962 (0)6 552 7140, 553 0229, 551 4037
Fax: +962 (0)6 553 6560
E-mail: terraco@nol.com.jo
Web: www.terraco.jo

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
Tel: +20 (0)2 8340 004, 832 3584
Fax: +20 (0)2 8340 004, 832 3584
E-mail: terraco@terraco.com.eg

UAE:

Terraco UAE Ltd
Tel: +971 (0)6 543 3565
Fax: +971 (0)6 543 3558
E-mail: terraco@emirates.net.ae

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
Tel: +90 (0)222 236 0423
Fax: +90 (0)222 236 0425
E-mail: terraco@terraco.com.tr
Web: www.terraco.com.tr

THAILAND:

Terraco Industry (Thailand) Limited
Tel: +66 (0)2 948 5558
Fax: +66 (0)2 948 5540
E-mail: terraco@terraco.co.th

VIETNAM:

Terraco Vietnam Co., Ltd
Tel: +84 (0)650 820100
Fax: +84 (0)650 820101
E-mail: terraco_vietnam@hcm.vnn.vn

SOUTH KOREA:

Terraco Korea Co., Ltd
Tel: +82 (0)43 645 8814
Fax: +82 (0)43 643 9429
E-Mail: terraco@terraco.co.kr
Web: www.terraco.co.kr

IRELAND:

Terraco Technical Centre, Ireland
Tel: +353 (0) 404 66555
Fax: +353 (0) 404 66654
E-mail: terraco@eircom.net
Web: www.terraco.com