

## OVERVIEW

Terragrout is a hard-wearing, water-resistant grout for filling joints in exterior and interior walls and floor tiles, mosaics and clinkers. It is specially formulated to fill joints of up to 5mm in width. It is easily applied by hand and because of its unique composition, does not shrink when dry. Terragrout is manufactured in 10 standard colours.

## PROPERTIES

Terragrout is composed of precisely graded, marble powder, a blend of special cements, water-repellent materials, oxide colours, plasticizers and polymers. Terragrout does not curl up during application and gives a water- and weather-resistant joint with no shrinkage cracks. All colours are light and lime fast.

## AREAS OF USE

Terragrout can be used on materials such as wall and floor tiles, clinkers and mosaics, where joints do not exceed 5mm in width.

## PREPARATION OF SURFACE

Ensure that all tile joints and edges are free and clean of excess tile fixing mortar and foreign matter.

## MIXING

Thoroughly mix Terragrout at the ratio of approximately 1ltr water to 4kg. Terragrout powder. Allow to stand for 15 minutes. Mix again. Terragrout is then ready for use.

## APPLICATION & CLEANING OF TOOLS

Wait until the Terrafix has set (approx. 24 hours) before grouting. Apply Terragrout diagonally into the joints with a rubber edged spatula. Remove excess grout with a moist sponge before drying. Do not apply Terragrout to an area which is so large that it cannot be completed within an hour. Porous tiles should be moistened with water before grouting. After Terragrout has dried and before it has hardened, polish the tiles with a clean, dry cloth leaving the joints flush with the tile. 24 hours after grouting, moisten the joints with a wet sponge.

Clean tools and equipment with water after use.

## HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

## PACKAGING & STORAGE

Terragrout is supplied powder form in 5kg and 20kg valve bags.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 6 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

## TECHNICAL DATA

<b>Product</b>	Tile grouting compound for joints up to 5mm.
<b>Binders</b>	Hydraulic/latex.
<b>Filler</b>	Crushed, precisely graded extenders.
<b>Colours</b>	Available in 10 standard colours.
<b>Pigments</b>	Fast to light, lime, salt and cement.
<b>Material Consumption</b>	0.5 - 1.0kg per m <sup>2</sup> depending upon width of tile joints.
<b>Water Consumption</b>	Approximately 1ltr clean water to 4kg Terragrout powder.
<b>Packaging</b>	Supplied in powder form in 5kg and 20kg valve bags.
<b>Storage</b>	6 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

### RUSSIA:

OOO Terraco Sweden Ltd, Russia  
 Tel: +7 095 101 2237  
 Fax: +7 095 927 3881  
 E-mail: terraco@online.ru  
 Web: www.terraco.ru

### OOO Terraco Vostok Ltd

Tel: +7 (0)4212 431 933  
 Fax: +7 (0)4212 431 977  
 E-mail: terracoVostok@terraco.khn.ru

### CHINA:

Terraco Architectural Coatings China Co., Ltd.  
 Tel: +86 (0)20 8758 2600,  
 Fax: +86 (0)20 8526 8056  
 E-mail: sales@terraco.com.cn  
 Web: www.terraco.com.cn

### Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 6210 2048  
 Fax: +86 (0)21 6252 0547  
 Email: sales@terraco.com.cn

### JORDAN:

Jordan Swedish Polymers Industrial Corp.  
 Tel: +962 (0)6 552 7140, 553 0229, 551 4037  
 Fax: +962 (0)6 553 6560  
 E-mail: terraco@nol.com.jo  
 Web: www.terraco.jo

### EGYPT:

Terraco Egypt Chemical Industries S.A.E.  
 Tel: +20 (0)2 8340 004, 832 3584  
 Fax: +20 (0)2 8340 004, 832 3584  
 E-mail: terraco@terraco.com.eg

### UAE:

Terraco UAE Ltd  
 Tel: +971 (0)6 543 3565  
 Fax: +971 (0)6 543 3558  
 E-mail: terraco@emirates.net.ae

### TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS  
 Tel: +90 (0)222 236 0423  
 Fax: +90 (0)222 236 0425  
 E-mail: terraco@terraco.com.tr  
 Web: www.terraco.com.tr

### THAILAND:

Terraco Industry (Thailand) Limited  
 Tel: +66 (0)2 948 5558  
 Fax: +66 (0)2 948 5540  
 E-mail: terraco@terraco.co.th

### VIETNAM:

Terraco Vietnam Co., Ltd  
 Tel: +84 (0)650 820100  
 Fax: +84 (0)650 820101  
 E-mail: terraco\_vietnam@hcm.vnn.vn

### SOUTH KOREA:

Terraco Korea Co., Ltd  
 Tel: +82 (0)43 645 8814  
 Fax: +82 (0)43 643 9429  
 E-Mail: terraco@terraco.co.kr  
 Web: www.terraco.co.kr

### IRELAND:

Terraco Technical Centre, Ireland  
 Tel: +353 (0) 404 66555  
 Fax: +353 (0) 404 66654  
 E-mail: terraco@eircom.net  
 Web: www.terraco.com