

OVERVIEW

Terrashield Super is a high-quality, weather-resistant acrylic paint, suitable for use without a primer on exterior and interior surfaces of concrete, plywood, anti-rust primed steel, etc. Terrashield Super gives outstanding economy with the advantage of a low material consumption rate and excellent adhesion. Terrashield Super is algal and fungal resistant. Application is by brush, roller, airless or conventional spray. Terrashield Super is available in 20 colours. Other colours can be matched on request.

PROPERTIES

Terrashield Super contains materials which provide excellent weather and pollution-resistant properties, as well as precisely graded marble powder to ensure the coated surface always maintains its original decorative beauty. Terrashield Super has a matt finish when dry.

AREAS OF USE

Terrashield Super can be used on new or old surfaces of concrete, brickwork, plasterwork, plywood, galvanised steel and anti-rust primed steel. It is suitable for housing developments, industrial and commercial complexes, bridge facades, girders and roof trusses, site cabins, etc.

PREPARATION OF SURFACE

Ensure that dust, dirt and foreign matter are brushed away. Also ensure that the surface is solid, free from salts, oil, grease and ridges. Protect all adjacent surfaces not to be painted. All cracks, chips, voids and damages should be repaired with a filler prior to painting. Handycoat Interior or Handycoat Exterior are recommended.

PRIMING

Priming new or old work is not necessary, but in order to stabilise a surface which shows signs of dusting or flaking, the use of TERRACO Penetrating Primer is recommended.

APPLICATION & CLEANING OF TOOLS

When applying to old painted surfaces, first wash down with a soda/water solution, rinse and allow to dry before either patching or painting. Very porous substrates should be filled and may require a diluted first coat. Apply the paint by brush, roller or spray. The application operation should be continuous in order to avoid dry edges; therefore plan the application work accordingly.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Terrashield Super is supplied in 5kg and 20kg containers.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Premium quality exterior masonry paint.
Binder	Acrylic.
Pigments	Lime and light-fast. Weather and pollution-resistant.
Colours	According to TERRACO colour charts. Any special colours can be matched on request.
Dilution	With water if necessary. For a two coats application, the first coat may be diluted with 10% water.
Viscosity	10,000 - 15,000cps
Specific Gravity	1:40 ± 0.05
Solid Content	55% ± 3%
pH Value	8-8.5
Application Method	Spray (airless or conventional), brush or roller.
Coverage	Approximately 200grs/m ² /coat.
Packaging	5kg and 20kg plastic pails.
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

RUSSIA:

OOO Terraco Sweden Ltd, Russia
Tel: +7 095 101 2237
Fax: +7 095 927 3881
E-mail: terraco@online.ru
Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 431 933
Fax: +7 (0)4212 431 977
E-mail: terracoVostok@terraco.khn.ru

CHINA:

Terraco Architectural Coatings China Co., Ltd.
Tel: +86 (0)20 8758 2600,
Fax: +86 (0)20 8526 8056
E-mail: sales@terraco.com.cn
Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 6210 2048
Fax: +86 (0)21 6252 0547
Email: sales@terraco.com.cn

JORDAN:

Jordan Swedish Polymers Industrial Corp.
Tel: +962 (0)6 552 7140, 553 0229, 551 4037
Fax: +962 (0)6 553 6560
E-mail: terraco@nol.com.jo
Web: www.terraco.jo

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
Tel: +20 (0)2 8340 004, 832 3584
Fax: +20 (0)2 8340 004, 832 3584
E-mail: terraco@terraco.com.eg

UAE:

Terraco UAE Ltd
Tel: +971 (0)6 543 3565
Fax: +971 (0)6 543 3558
E-mail: terraco@emirates.net.ae

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
Tel: +90 (0)222 236 0423
Fax: +90 (0)222 236 0425
E-mail: terraco@terraco.com.tr
Web: www.terraco.com.tr

THAILAND:

Terraco Industry (Thailand) Limited
Tel: +66 (0)2 948 5558
Fax: +66 (0)2 948 5540
E-mail: terraco@terraco.co.th

VIETNAM:

Terraco Vietnam Co., Ltd
Tel: +84 (0)650 820100
Fax: +84 (0)650 820101
E-mail: terraco_vietnam@hcm.vnn.vn

SOUTH KOREA:

Terraco Korea Co., Ltd
Tel: +82 (0)43 645 8814
Fax: +82 (0)43 643 9429
E-Mail: terraco@terraco.co.kr
Web: www.terraco.co.kr

IRELAND:

Terraco Technical Centre, Ireland
Tel: +353 (0) 404 66555
Fax: +353 (0) 404 66654
E-mail: terraco@eircom.net
Web: www.terraco.com