

OVERVIEW

Terratop is high quality interior/exterior grade vinyl emulsion paint for use on most building surfaces. Terratop offers the advantage of low material consumption with a luxurious satin finish and is available in a range of 20 attractive shades.

PROPERTIES

Terratop is based on acrylic co-polymer resins and high quality pigments to ensure excellent colour opacity, brushability and washability. The finish has an attractive lustre and is ideal for high quality finishing works.

AREAS OF USE

Terratop can be used on new or old interior and exterior surfaces of concrete, brickwork, plasterwork, sprayplasters and plywood. It is suitable for housing developments, industrial and commercial complexes, Porto-cabin interiors, etc.

PREPARATION OF SURFACE

Ensure that dust, dirt and foreign matter are brushed and scraped away. Also ensure that the surface is solid, free from salt, oil, grease and ridges. Protect all adjacent areas not to be painted. All cracks, chips, voids and damages should be repaired with TERRACO Handycoat Interior or Handycoat Exterior prior to painting.

PRIMING

Dusty and flaking surfaces should be primed with TERRACO Penetrating Primer.

APPLICATION & CLEANING OF TOOLS

When applying to old painted surfaces, first wash down with a soda/water solution, rinse and allow to dry before either patching or painting. Very porous substrates should be filled and may require a diluted first coat. Apply the paint by brush, roller or spray.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Terratop is supplied in 5kg and 20kg containers.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Vinyl silk emulsion
Binder	Acrylic co-polymer.
Colours	20 standard colours, specials available on request
Drying Time	1 - 2 hours.
Viscosity	6,000cps.
Specific Gravity	1:27
Coverage	200-250grs/m ² .
Dilution	With water up to 20%.
Packaging	5kg and 20kg plastic pails.
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

RUSSIA:

OOO Terraco Sweden Ltd, Russia
 Tel: +7 095 101 2237
 Fax: +7 095 927 3881
 E-mail: terraco@online.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 431 933
 Fax: +7 (0)4212 431 977
 E-mail: terracoVostok@terraco.khn.ru

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8758 2600,
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 6210 2048
 Fax: +86 (0)21 6252 0547
 Email: sales@terraco.com.cn

JORDAN:

Jordan Swedish Polymers Industrial Corp.
 Tel: +962 (0)6 552 7140, 553 0229, 551 4037
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
 Tel: +20 (0)2 8340 004, 832 3584
 Fax: +20 (0)2 8340 004, 832 3584
 E-mail: terraco@terraco.com.eg

UAE:

Terraco UAE Ltd
 Tel: +971 (0)6 543 3565
 Fax: +971 (0)6 543 3558
 E-mail: terraco@emirates.net.ae

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
 Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

THAILAND:

Terraco Industry (Thailand) Limited
 Tel: +66 (0)2 948 5558
 Fax: +66 (0)2 948 5540
 E-mail: terraco@terraco.co.th

VIETNAM:

Terraco Vietnam Co., Ltd
 Tel: +84 (0)650 820100
 Fax: +84 (0)650 820101
 E-mail: terraco_vietnam@hcm.vnn.vn

SOUTH KOREA:

Terraco Korea Co., Ltd
 Tel: +82 (0)43 645 8814
 Fax: +82 (0)43 643 9429
 E-Mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

IRELAND:

Terraco Technical Centre, Ireland
 Tel: +353 (0) 404 66555
 Fax: +353 (0) 404 66654
 E-mail: terraco@eircom.net
 Web: www.terraco.com