

OVERVIEW

TimberLac is an interior acrylic wood varnish which is both easy to use and quick drying. TimberLac is available as a clear finish in gloss, satin and matt. If colour is required TimberStain is first used to stain the wood, after which TimberLac is applied in 2 to 3 coats. The full job can be completed in 1 day due to its fast drying nature. Clean-up is with water.

PROPERTIES

TimberLac is an acrylic based lacquer coating for interior wood with the following properties:

- Tough durable finish
- Quick drying
- 3 coat application in 1 day
- Easy to apply

AREA OF USE

All interior wood subject to medium to light wear.

PREPARATION OF SURFACE

Remove all traces of grease, wax or polish by washing with white spirits. On new surfaces ensure that nails are punched below surface and all holes are filled with suitable wood filler. Sand in the direction of grain and remove any dust with a lint free cloth.

PRODUCT GRADES/CODES

Gloss	62610
Satin	62612
Matt	62614

STAINING

If colour is required use TimberStain. See data sheet for application instructions.

APPLICATION & CLEANING OF TOOLS

Stir thoroughly before use. Apply using a brush or short pile roller finishing in the direction of the grain. Leave for 2 to 4 hours between coats. Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

TimberLac is supplied in 1ltr, 2.5ltr, 5ltr and 20ltr containers.

TimberLac should be stored in a clean, dry area, protected from direct sunlight and extreme heat or cold. Unopened containers can be stored for 12 months. Ensure that oldest material is used first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Acrylic quick drying interior wood varnish.
Sheen	Gloss, satin and matt..
Colour	Clear.
Binder	Acrylic .
Clean-up	With water.
Touch Dry	1 to 2 hours.
Re-coat	2 to 4 hour.
Coverage	New wood 50-100 grs/m ² . Previously coated 40-50 grs/m ²
Packaging	1ltr, 2.5ltr and 5ltr containers.
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

RUSSIA:

OOO Terraco Sweden Ltd, Russia
 Tel: +7 095 101 2237
 Fax: +7 095 927 3881
 E-mail: terraco@online.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd
 Tel: +7 (0)4212 431 933
 Fax: +7 (0)4212 431 977
 E-mail: terracoVostok@terraco.khn.ru

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8758 2600,
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.
 Tel: +86 (0)21 6210 2048
 Fax: +86 (0)21 6252 0547
 Email: sales@terraco.com.cn

JORDAN:

Jordan Swedish Polymers Industrial Corp.
 Tel: +962 (0)6 552 7140, 553 0229, 551 4037
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
 Tel: +20 (0)2 8340 004, 832 3584
 Fax: +20 (0)2 8340 004, 832 3584
 E-mail: terraco@terraco.com.eg

UAE:

Terraco UAE Ltd
 Tel: +971 (0)6 543 3565
 Fax: +971 (0)6 543 3558
 E-mail: terraco@emirates.net.ae

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
 Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

THAILAND:

Terraco Industry (Thailand) Limited
 Tel: +66 (0)2 948 5558
 Fax: +66 (0)2 948 5540
 E-mail: terraco@terraco.co.th

VIETNAM:

Terraco Vietnam Co., Ltd
 Tel: +84 (0)650 820100
 Fax: +84 (0)650 820101
 E-mail: terraco_vietnam@hcm.vnn.vn

SOUTH KOREA:

Terraco Korea Co., Ltd
 Tel: +82 (0)43 645 8814
 Fax: +82 (0)43 643 9429
 E-Mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

IRELAND:

Terraco Technical Centre, Ireland
 Tel: +353 (0) 404 66555
 Fax: +353 (0) 404 66654
 E-mail: terraco@eircom.net
 Web: www.terraco.com