

OVERVIEW

TimberStain is a water based wood dye used for staining wood prior to application of TimberLac or DiamondGlaze. It is available in a range of seven attractive wood tones and can be overcoated in 2 hours. Application is easy and clean-up is with water.

PROPERTIES

Terraco TimberStain is a water based acrylic preparation of transparent iron oxides and other wood colourants. Terraco TimberStain has the following properties:

- Attractive colour range
- Quick drying
- Easy to apply
- Can also be used to colour wood filler
- Fade resistant colours

AREAS OF USE

As an interior wood dye used in conjunction with TimberLac and DiamondGlaze.

PREPARATION OF SURFACE

Remove all traces of grease, wax or polish by washing with white spirits. On new surfaces ensure that nails are punched below surface and all holes are filled with suitable wood filler. Sand in the direction of grain and remove any dust with a lint free cloth.

APPLICATION & CLEANING OF TOOLS

Stir well before use. Apply TimberStain using a sponge or lint free cloth. Rub well into the wood and finish in the direction of grain. TimberStain is touch dry in 20 minutes and can be overcoated after 1 hour.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Terraco TimberStain is supplied in 1ltr, 2.5ltr, 5ltr and 20ltr containers.

Terraco TimberStain should be stored in a clean, dry area, protected from direct sunlight and extreme heat or cold. Unopened containers can be stored for 12 months. Ensure that oldest material is used first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Water based wood dye.
Colours	Pine, oak, mahogany, teak, chestnut, walnut and rosewood.
Binder	Acrylic.
Pigments	Transparent iron oxides.
Clean-up	With water.
Touch Dry	20 minutes.
Re-coat	1 hour.
Coverage	50-100 grs/m ²
Packaging	1ltr, 2.5ltr, 5ltr and 20ltr containers.
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

RUSSIA:

OOO Terraco Sweden Ltd, Russia
 Tel: +7 095 101 2237
 Fax: +7 095 927 3881
 E-mail: terraco@online.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 431 933
 Fax: +7 (0)4212 431 977
 E-mail: terracoVostok@terraco.khn.ru

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8758 2600,
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 6210 2048
 Fax: +86 (0)21 6252 0547
 Email: sales@terraco.com.cn

JORDAN:

Jordan Swedish Polymers Industrial Corp.
 Tel: +962 (0)6 552 7140, 553 0229, 551 4037
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
 Tel: +20 (0)2 8340 004, 832 3584
 Fax: +20 (0)2 8340 004, 832 3584
 E-mail: terraco@terraco.com.eg

UAE:

Terraco UAE Ltd
 Tel: +971 (0)6 543 3565
 Fax: +971 (0)6 543 3558
 E-mail: terraco@emirates.net.ae

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
 Tel: +90 (0)222 236 0423
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

THAILAND:

Terraco Industry (Thailand) Limited
 Tel: +66 (0)2 948 5558
 Fax: +66 (0)2 948 5540
 E-mail: terraco@terraco.co.th

VIETNAM:

Terraco Vietnam Co., Ltd
 Tel: +84 (0)650 820100
 Fax: +84 (0)650 820101
 E-mail: terraco_vietnam@hcm.vnn.vn

SOUTH KOREA:

Terraco Korea Co., Ltd
 Tel: +82 (0)43 645 8814
 Fax: +82 (0)43 643 9429
 E-Mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

IRELAND:

Terraco Technical Centre, Ireland
 Tel: +353 (0) 404 66555
 Fax: +353 (0) 404 66654
 E-mail: terraco@eircom.net
 Web: www.terraco.com